#### BLIS.R16754 - CAULKING AND SEALANTS

### Caulking and Sealants

See General Information for Caulking and Sealants

#### **DEWALT INDUSTRIAL TOOL CO**

R16754

701 E Joppa Rd Towson, MD 21286 USA Foamed plastic caulking and sealant.

# PowerFoam Residential Grade Applied to Inorganic Reinforced Cement Board+

Flame spread	10
Smoke developed	30

<sup>+</sup>Tested as applied in three 3/4 in. diameter beads, 5 in. OC covering 12.5 percent of the exposed test sample area.

# TriggerFoam Pro Standard Applied to Inorganic Reinforced Cement Board+

Flame spread	5
Smoke developed	10

<sup>+</sup>Tested as applied in three 3/4 in. diameter beads, 5 in. OC covering 12.5 percent of the exposed test sample area.

# TriggerFoam Pro Window and Door Applied to Inorganic Reinforced Cement Board+

Flame spread	0
Smoke developed	10

<sup>+</sup>Tested as applied in three 3/4 in. diameter beads, 5 in. OC covering 12.5 percent of the exposed test sample area.

# TriggerFoam Pro All Season Applied to Inorganic Reinforced Cement Board+

Flame spread	0
--------------	---

+Tested as applied in three 3/4 in. diameter beads, 5 in. OC covering 12.5 percent of the exposed test sample area.

# Trigger Foam Pro Fire Block Applied to Inorganic Reinforced Cement Board+

Flame spread	0
Smoke developed	10

<sup>+</sup>Tested as applied in three 3/4 in. diameter beads, 5 in. OC covering 12.5 percent of the exposed test sample area.

# Trigger Foam Pro Window & Door Applied to Inorganic Reinforced Cement Board+

Flame spread	0
Smoke developed	10

<sup>+</sup>Tested as applied in three 3/4 in. diameter beads, 5 in. OC covering 12.5 percent of the exposed test sample area.

## Trigger Foam Pro All Season Applied to Inorganic Reinforced Cement Board+

Flame spread	0
Smoke developed	10

<sup>+</sup>Tested as applied in three 3/4 in. diameter beads, 5 in. OC covering 12.5 percent of the exposed test sample area.

Last Updated on 2016-12-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"