Flat Hd w/Nibs, Square Recess DECK SCREWS W/TYPE-17 POINT



Flat Hd w/Nibs, Square Recess Deck Screw with Type-17 Point

Nominal Diameter	A		R		D		S	Recess Size
	Head Diameter		Recess Depth		Major Thread Diameter		Shoulder Diameter	
	Max	Min	Max	Min	Max	Min	Ref	
8	0.311	0.286	0.075	0.064	0.177	0.157	0.124	2
9	0.336	0.308	0.075	0.064	0.177	0.169	0.126	2
10	0.378	0.341	0.075	0.064	0.199	0.186	0.137	2

Tolerance on Length	
Up to 1.25”	+0 / -0.05
Over 1.25 to 2.5”	+0 / -0.07
Over 2.5 to 4”	+0 / -0.10

Description	An externally threaded fastener with a countersunk head, square socket recess and a single lead thread. The bearing surface of the countersink has several equidistant nibs running down the underside of the head from the top, outer edge. The shank has a full body diameter and a chip cavity cut out where the final several threads end at the tip.
Applications / Advantages	The deeper thread design offers greater resistance to pull-out forces. The chip cavity (or auger point) enables the fastener to drive—especially in denser woods—without pre-drilling a pilot hole.
Material	18-8 Stainless steel
Plating	Stainless Deck screws have a commercial passivation.